



# T360LED

PAGODA LED LUMINAIRE

**JOB INFORMATION**

Type: \_\_\_\_\_

Catalog No: \_\_\_\_\_

Project Name: \_\_\_\_\_

Comments: \_\_\_\_\_

Prepared by: \_\_\_\_\_

T360LED

**FEATURES**

**USE OF PRODUCT**

The intended use of this product is for parking lots, roadways, public parking areas, or public access areas.

**HOUSING**

Heavy gauge spun aluminum housing with spun aluminum hood.

**FINISH**

Matt-finished, thermoset polyester oven baked powdercoat. Available in standard dark polyester bronze finish or consult factory for made to order architectural finishes

**OPTICS**

“Hi-vue”, clear lens available in acrylic lens.

**LED**

High output LEDs offer a minimum estimated operating life of 50,000 hours in 3000K, 3500K, 4000K, or 5000K with CRI>83. LEDs placed on high performance aluminum heatsink for reduced junction temperatures and extended life.

**DRIVER**

Durable LED driver operates at 120-277V with 0-10V dimming protocol. Power factor: 0.90; 50 to 60 Hz. Driver protections includes: Output open load, over-current and short-circuit, and

over-temperature with auto recovery. -30°C Min Temp. 40°C Max Temp. Step down transformer may be utilized for 480V or 347V applications.

**EPA**

Effective Projected Area (Sq. Ft.):  
Type A: 2.333 ft^2 (1 fixture),  
Type B: 4.128 ft^2 (1 fixture)

**MOUNTING**

Fixture pole must be mounted on a concrete base (supplied by others). Aluminum Slip-fitter is available up to 4” OD upon request.

**LISTINGS/COMPLIANCE**

- CEC Compliant emergency driver
- CSA - Suitable for wet locations.

**B.U.G. RATING**

Watts	Lumens	B-U-G Rating
10W	1050lm	B1-U2-G0
18W	1890lm	B1-U2-G0
30W	3150lm	B2-U2-G1
45W	4725lm	B2-U3-G1
57W	5985lm	B3-U3-G1

SERIES	SIZE	WATT/LUMENS	VOLTAGE	COLOR TEMPERATURE	LENS	MOUNTING	FINISH	OPTIONS
T360LED	A - 14"	10 - 10W/1050lm	UNV - 120V-277V	30 - 3000K	A <sup>1</sup> - Acrylic	40D - 4" Post top OD	BZ <sup>2</sup> - Bronze	PC - Photocell 120-277V
	B - 23"	18 - 18W/1890lm	347 - 347V	35 - 3500K		MT0 - Made to order	MT0 <sup>3</sup> - Made to order	MS - Motion Sensor (Bi-Level)
		30 - 30W/3150lm	480 - 480V	40 - 4000K			MGTO <sup>3</sup> - Marin grade made to order	EM - Emergency battery
		45 - 45W/4725lm		50 - 5000K				SP10 - Surge Protection 10KV
		57 - 57W/5985lm						BS - Bird Spikes

**Notes**  
1. Standard lens.  
2. Standard finish.  
3. RAL number required.

**Notes**  
1. Standard finish.  
2. RAL number required.

# T360LED

PAGODA LED LUMINAIRE

DIMENSIONS

